

## KLIPSCH SPEAKER SYSTEMS

Surround Speaker	Sub Woofer	Centre Speaker	Front and Rear Speakers
			
<p><b>FREQ RESPONSE:</b> 62Hz-23kHz +/-3dB</p> <p><b>POWER HANDLING:</b> 100W RMS / 400W Peak</p> <p><b>SENSITIVITY:</b> 95dB @ 2.83V / 1m (equivalent sound energy)</p> <p><b>NOMINAL IMPEDANCE:</b> 8 ohms compatible</p> <p><b>HIGH FREQ DRIVERS:</b> Dual 1" (2.54cm) Titanium diaphragm compression drivers mated to 90x60 square Tractrix® Horns</p> <p><b>HIGH FREQ CROSSOVER:</b> 1700Hz</p> <p><b>LOW FREQ DRIVERS:</b> Dual 5.25" (13.3cm) Cerametallic™ cone woofers</p> <p><b>ENCLOSURE TYPE:</b> Bass-reflex via dual side-firing ports</p> <p><b>HxWxD:</b> 33cmx32cmx21.6cm</p> <p><b>MOUNTING:</b> Keyhole bracket and Dual 1/4"-20 threaded inserts</p> <p><b>WEIGHT:</b> 15lbs (6.8kg)</p> <p><b>FINISHES:</b> Matte Black vinyl</p>	<p><b>FREQ RESPONSE:</b> 24-120Hz +/-3dB</p> <p><b>MAXIMUM ACOUSTIC OUTPUT:</b> 116dB @ 30Hz 1/8 space, 1m</p> <p><b>AMPLIFIER POWER:</b> FTC Rated Power: 350 watts continuous @ &lt;2% THD / Dynamic Power*: 825 watts</p> <p><b>DRIVE COMPONENTS:</b> 12" (30.5cm) Cerametallic™ cone, front-firing woofer</p> <p><b>AMPLIFIER:</b> BASH® digital hybrid</p> <p><b>ENCLOSURE TYPE:</b> Bass-reflex via front-firing CornerPort™</p> <p><b>INPUTS:</b> L/R Line-level RCA jacks, L/R High-level speaker binding posts</p> <p><b>OUTPUTS:</b> None</p> <p><b>DIMENSIONS:(HxWxD)</b> 48.8cmx37.1cmx53.3cm</p> <p><b>WEIGHT:</b> 49lbs (22.2kg)</p> <p><b>FEATURES:</b> DCS control and feature set w/ 3 system presets</p> <p><b>FINISHES:</b> Black Ash woodgrain vinyl</p> <p><b>FEATURES:</b> DCS control and feature set w/ 3 system presets</p>	<p><b>FREQ RESPONSE:</b> 57Hz-23kHz +/-3dB</p> <p><b>POWER HANDLING:</b> 150W RMS / 600W Peak</p> <p><b>SENSITIVITY:</b> 98dB @ 2.83V / 1m</p> <p><b>NOMINAL IMPEDANCE:</b> 8 ohms compatible</p> <p><b>HIGH FREQ DRIVERS:</b> 1" (2.54cm) Titanium diaphragm compression driver mated to 90x60 square Tractrix® Horn</p> <p><b>HIGH FREQ CROSSOVER:</b> 1150Hz, 1650Hz</p> <p><b>LOW FREQ DRIVERS:</b> Dual 6.5" (16.5cm) Cerametallic™ cone woofers</p> <p><b>ENCLOSURE TYPE:</b> Bass-reflex via dual front-firing ports</p> <p><b>HxWxD:</b> 20.3cmx59.7cmx31.8cm</p> <p><b>MOUNTING:</b> Uptilt and Downtilt feet</p> <p><b>WEIGHT:</b> 32lbs (14.5kg)</p> <p><b>FINISHES:</b> Cherry or Black Ash woodgrain vinyl</p>	<p><b>FREQ RESPONSE:</b> 38Hz-23kHz +/-3dB</p> <p><b>POWER HANDLING:</b> 125W RMS / 500W Peak</p> <p><b>SENSITIVITY:</b> 97dB @ 2.83V / 1m</p> <p><b>NOMINAL IMPEDANCE:</b> 8 ohms compatible</p> <p><b>HIGH FREQ DRIVERS:</b> 1" (2.54cm) Titanium diaphragm compression driver mated to 90x60 square Tractrix® Horn</p> <p><b>HIGH FREQ CROSSOVER:</b> 1800Hz</p> <p><b>LOW FREQ DRIVERS:</b> Dual 6.5" (16.5cm) Cerametallic™ cone woofers</p> <p><b>ENCLOSURE TYPE:</b> Bass-reflex via dual rear-firing ports</p> <p><b>HxWxD:</b> 103.1cmx21.6cmx39.4cm (w/feet)</p> <p><b>WEIGHT:</b> 54lbs (24.5kg)</p> <p><b>FINISHES:</b> Black Ash woodgrain vinyl</p>